



## CDC 500



WHEN COMPETITIVENESS COUNTS

### PRODUCTION CAPACITY

- Cycle time .....: - 5 → 6 minutes
- Lenses / cycle .....: 6 → 8
- Lenses / hour .....: 60 → 80
- Type of lenses .....: all types Ø 40 to 80 mm

**SCL**  
international  
HARD COAT LEADER





### SPECIFICATIONS

- Limited foot print
- 1 single zone for cleaning and hard coating
- Automatic detergent, alcohol and varnish refilling
- Simple design for 1 or 2 shift use
- Remote connection to SCL service team
- Optimized water and energy consumption
- User friendly HMI

### BENEFITS

- For compact layout
- ISO6 coating chamber
- Easy maintenance, stable process and no production stop
- Easy maintenance
- Easier and faster diagnosis. Upgrading possibility
- Sustainable process

### TECHNICAL DATA

Machine splittable in 2 parts for shipment  
 Dimensions .....: 360 x 137 x 208 cm  
 Weight .....: ~ 750 kg  
 Electricity .....: ~ 5,9 kW / 400 V (3Ph + N + Gnd)  
 Compressed air.....: No  
 Flow machine left to right or from right to left  
 CE compliance

### PERIPHERALS

- Chillers to maintain the coating temperature +5 → +20°C
- Curing ovens : stand alone or in-line
- Automatic osmosis unit for ultra pure water production
- Draining tank with lift pump
- Ultrasonic stripping for lenses and racks : stand alone or automatic cleaning machine
- A/C unit for coating zone
- Ergonomic preparation/control station
- Lens-holders and rack for 6 or 8 lenses



[www.scl-intl.com](http://www.scl-intl.com)

**SCL**  
international

HARD COAT LEADER

