





TINTING AT ITS BEST

PRODUCTION CAPACITY

- Lenses / rack : 10
- Type of lenses : all types Ø 40 to 80mm
- Tinting tank capacity .. : 5 liters

SCL
international
HARD COAT LEADER





SPECIFICATIONS

- Up to 10 tinting tanks according to needs
- From 2 to 10 digital gradient systems
- Stirring by rotating magnet
- Electropolished stainless steel tinting tanks
- Accurate temperature control +/- 1°C
- Tank removable easily
- Flexible drain with 3 ways valve (can or sewage)
- Modular extraction of the tinting vapours
- Possibility to custom the size and position of the gradient
- User friendly HMI

BENEFITS

- A modular system according to needs
- Easy to clean
- For stable results
- For an easy maintenance
- Adaptable system
- Safe working station
- Make any gradient wished
- Gradient profile easy to be defined
- Create the recipes
- Follow in live the cycle

TECHNICAL DATA

Machine in 1 part
 Dimensions: 250 cm x 92 cm x 215 cm
 Weight: ~ 500 kg
 Electricity: 12 kW / 400 V
 Compressed air: No
 CE compliance

PERIPHERALS

- Water softener (raw water supply)
- Draining tank with lift pump
- Ergonomic preparation/control station
- Lens-holders and rack for 10 lenses



www.scl-intl.com

SCL
international

HARD COAT LEADER

