



HCC5



AFFORDABLE AND COMPETITIVE

PRODUCTION CAPACITY

- Cycle time: - 5 minutes
- Lenses / cycle: 6
- Lenses / hour: 60
- Type of lenses: all types Ø 40 to 80 mm

SCL
international
HARD COAT LEADER





SPECIFICATIONS

- Minimal foot print and compact design
- 1 single zone for cleaning and hard coating
- Automatic detergent and alcohol refilling
- Optimized water and energy consumption
- User friendly HMI

BENEFITS

- For compact layout
- ISO6 coating chamber
- Easy maintenance, stable process and no production stop
- Sustainable process

TECHNICAL DATA

Machine in 1 part
 Dimensions: 330 x 125 x 208 cm
 Weight: ~ 750 kg
 Electricity: 10,3 kW / 400 V (3Ph + N + Gnd)
 Compressed air: No
 Flow machine left to right or from right to left
 CE and UL compliance

PERIPHERALS

- Chillers to maintain the coating temperature +5 → +20°C
- Curing ovens : stand alone or in-line
- Automatic osmosis unit for ultra pure water production
- Draining tank with lift pump
- Ultrasonic stripping for lenses and racks:
stand alone or automatic cleaning machine
- A/C unit for coating zone
- Ergonomic preparation/control station
- Lens holders and rack for 6 lenses



www.scl-intl.com



HARD COAT LEADER

